

# AQUABLAST® - PLUS surface cleaner

## Type FRV 3000

- Available with and without direct vacuuming of water and waste material
- Spray bar driven by reaction force of the water jets
- Height adjustable spray bar
- Wear resistant rotary action with dynamic high pressure seal
- Spray bar housing with special seal and suction outlets
- Electrical pressure on/off control

## Typical applications

- Direct vacuuming allows the use of high pressure water in factories and machine shops without halting production or on roads, upper storeys of buildings etc. without the need for closure
- Cleaning PLUS vacuuming of petrol, oil and grease deposits



## Marine industry

- Removal PLUS vacuuming of paint, deck coatings, rust etc.



Nozzle inserts  
Type "P"

## Construction industry

- Removal PLUS vacuuming of paints, mastics, laitence, adhesion inhibitors, renderings etc.
- Brightening PLUS vacuuming of thermoplastic flooring
- Scarifying PLUS vacuuming of concrete and asphalt

## Technical data

Working width: 215 mm  
 Operating pressure: max. 3000 bar  
 Flow rate: max. 40 l/min.  
 Pressure loss at 40 l/min: 60 bar  
 Pump power: max. 100 kW  
 Speed of rotation: max. 2500 r.p.m.  
 Nozzle insert design: P

Weight with 10 m suction hose: 130 kg  
 Length: approx. 1430 mm  
 Height: approx. 960 mm

Connections:  
 Bypass control cable: ITT-plug  
 High pressure hose: M 14 x 1,5 LH  
 Suction hose: B coupling

Description	Code-no.
electrical with suction and high pressure hose assy.	<b>09.00680.0015</b>
Without hose assy.	<b>09.00680.0014</b>

**Hammelmann**  
 Maschinenfabrik GmbH

Postfach 3309 • D-59282 Oelde    Telefon (0 25 22) 76-0  
 Zum Sundern 13-21 • Germany    Telefax (0 25 22) 76-444  
 eMail: mail@hammelmann.de • Internet: www.hammelmann.de

